

Optical Service Cable for XTENDR HFC Repeater

XT-SC SERIES

Lindsay Broadband has specifically designed the XT-SC series of optical service cables for the XTENDR HFC repeater.

The XT-SC series service cables use 6.2 mm diameter OFNR/FT4 unarmored outdoor black jacket distribution cable with bend-insensitive enhanced single-mode fiber with LC connectors on the fan-out.

The specially designed nickel plated brass feed-through 5/8" x 24 housing adapter prevents cable and transition cables from twisting.



XT-SC-8-xx-LA
(top view)

FEATURES

- 5/8" x 24 feed-through adapter prevents cable rotation during installation
- Fully waterblocked
- 6.2 mm tight buffered unarmored fiber cable
- 2.5 inch (64 cm) bending radius (no load)
- Bend-insensitive G.657A2 ESMF fiber
- LC/APC connectors
- Available in 2, 4 or 8 fibers
- Available in 10, 15, 30 or 50 meter lengths
- 100% tested for insertion loss & return loss
- Telcordia GR-326 & GR-20 compliant

ORDERING INFORMATION

	# of Fibers	Cable Length (meters)	Connector
XT-SC	x	xx	LA
	2	10 = 10 m	LA = LC/APC
	4	15 = 15 m	
	8	30 = 30 m	
		50 = 50 m	